



Plastic Bottle, 15 fl. oz.
078698305509

Metal Drum, 55 gal.
078698217314

HEAVY DUTY BLOCK SEAL

C616, C655

Repairs cracked blocks, cylinder heads, valve ports, water jackets in cars, trucks, diesel, tractors, marine and stationary engines of cooling systems up to 6-gallon capacity.

APPLICATIONS:

- Add to Radiator
- Repairs Cracked Engine Blocks & Cylinder Heads

DIRECTIONS: USE EXTREME CAUTION WHEN REMOVING RADIATOR CAP TO AVOID BURN INJURY CAUSED BY HIGH PRESSURE RELEASE OF HOT LIQUID OR STEAM. SEE OWNER'S MANUAL FOR CAP REMOVAL INSTRUCTIONS. Allow engine and cooling system to cool. Do not add liquids to hot radiator. If system contains anti-freeze, drain and save for re-use. If clean, flush system with clear water before using BLOCK SEAL. SEE DISPOSAL STATEMENT BELOW. If presence of rust, scale and sludge is evident, use MOTORMEDIC SUPER HEAVY DUTY RADIATOR CLEANER, flushing per product instructions. With cooling system clean, fill radiator with water, allowing room for expansion and addition of LIQUID BLOCK SEAL. Radiator hoses and thermostats need not be removed. Clamp off hoses to radiator heater core (heater). Shake package well before using. Pour contents into radiator, replace radiator cap and run engine until temperature is well above normal (180-200°F). Continue engine operation at high temperature (do not boil) for 5 to 10 minutes, or until visible leak stops. Drain entire system. Let repair set for 1/2 hour. Flush with clear water and then refill system. When used in accordance with directions, LIQUID BLOCK SEAL cannot impair circulation. For repairing combustion chamber cracks, remove spark plug from cracked section before starting engine.

STORAGE, HANDLING & DISPOSAL: Dispose of product, container, residue and used anti-freeze/coolant and radiator fluids in accordance with all local, state and federal laws and regulations. Never pour onto ground or into storm or septic systems.

DANGER: Wear safety goggles, protective gloves and avoid contamination of clothing.

FIRST AID: EYES: Flush with water for 15 minutes while lifting eyelids, and get prompt medical attention. SKIN: Wash with soap and water. If irritation persists, get prompt medical attention. INHALATION: Move to fresh air. If breathing becomes difficult, get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.